

# Uni DB1 Syntax Cheatsheet

Syntax cheatsheet for the DB1 (databases) course at HdM Stuttgart

---

Felicitas Pojtinger

2022-02-01

*“Come, let us go down and confuse their language so they will not understand each other” - Genesis 11:7, Die Bibel*

Mehr Details unter <https://github.com/pojntfx/uni-db1-notes>. Dieses Dokument ist nur als Schnell-Übersicht gedacht.

# Data Definition Language

---

```
create table persons (  
    person_id number primary key not null ,  
    first_name varchar2(50),  
    last_name varchar2(50) default 'Duck' not null  
);
```

```
drop table persons;
```

```
alter table persons rename to people;
```

```
alter table persons add ( phone varchar2(20), email varchar2
```

```
alter table persons modify ( birthdate date null, email varchar2(255) not null);
```



```
alter table persons drop column birthdate;
```

```
alter table purchase_orders add constraint purchase_orders_o
```

```
alter table purchase_orders drop constraint purchase_orders_
```

```
create view employees_years_of_service
as select
    employee_id, first_name || '␣' || last_name as full_name
    floor(months_between(current_date, hire_date) / 12) as y
from employees;
```

```
drop view employees_years_of_service;
```

```
create index members_full_name on members(first_name, last_name)
```

```
drop index members_full_name;
```

## Trigger erstellen

```
create trigger customers_credit_trigger
  before update of credit_limit
  on customers
declare
  current_day number;
begin
  current_day := extract(day from sysdate);

  if current_day between 28 and 31 then
    raise_application_error(-20100, 'Locked at the end of
end if;
end;
```



```
drop trigger customers_credit_trigger;
```

## Exceptions handle

```
create trigger users_ensure_trigger
  before update
  on users
  for each row
declare
  user_invalid exception;
  pragma exception_init(user_invalid, -20555);
begin
  raise user_invalid;

exception
  when user_invalid then
    raise_application_error(-20555, 'User is invalid');
  when others then
    dbms_output.put_line('Unexpected error: ' || sqlerrm);
end;
```

```
create or replace function get_my_sum( a integer, b integer
is
    multiplier number := 2;
begin
    return a + b * multiplier;
end;
```

```
select get_my_sum(1, 2) from dual;
```

```
drop function get_my_sum;
```

```
create or replace procedure get_sum ( a integer, b integer )
is
    multiplier number := 2;
    result number := 0;
begin
    result := a + b * multiplier;

    insert into results ( result ) values ( result );
end;
```

```
exec get_sum(1, 2);
```

```
drop procedure get_sum;
```



# Data Manipulation Language

---

- CHAR|CHARACTER (size)
- VARCHAR2 (size)
- DATE
- INTERVAL YEAR TO MONTH
- INTERVAL DAY TO SECOND
- INTEGER|INT
- NUMBER (precision [, scale ])
- FLOAT (precision)

```
insert into discounts(  
    discount_name,  
    amount,  
    start_date,  
    expired_date  
) values (  
    'Summer_Promotion',  
    9.5,  
    date '2017-05-01',  
    date '2017-08-31'  
)
```

```
update products  
set list_price = 420  
where list_price < 69;
```

```
delete from products  
where list_price > 69;
```

Gleiche Anzahl von Spalten, mehr Zeilen.

```
select
    first_name ,
    last_name ,
    email ,
    'contact' as role
from contacts
union select
    first_name ,
    last_name ,
    email ,
    'employee' as role
from employees order by role
```

Mehr Spalten & mehr Zeilen

```
select
    a.id as id_a,
    a.color as color_a,
    b.id as id_b,
    b.color as color_b
from palette_a a
inner join palette_b b using(color);
```



```
select
  a.id as id_a,
  a.color as color_a,
  b.id as id_b,
  b.color as color_b
from palette_a a
left outer join palette_b b using(color);
```

```
select
    a.id as id_a ,
    a.color as color_a ,
    b.id as id_b, b.color as color_b
from palette_a a
right outer join palette_b b using(color);
```

```
select
    a.id as id_a,
    a.color as color_a,
    b.id as id_b,
    b.color as color_b
from palette_a a
full outer join palette_b b using(color);
```

## Insert-Trigger

:old ist nicht vorhanden.

```
create or replace trigger customers_credit_trigger
  before insert of credit_limit
  on customers
declare
  current_day number;
begin
  current_day := extract(day from sysdate);

  if current_day between 28 and 31 then
    raise_application_error(-20100, 'Locked at the end of
  end if;
end;
```

```
create or replace trigger customers_credit_limit_trigger
  before update of credit_limit
  on customers
  for each row
  when (new.credit_limit > 0)
begin
  if :new.credit_limit >= 2*old.credit_limit then
    raise_application_error(-20101, 'The new credit cannot
  end if;
end;
```

## Delete-Trigger

:new ist nicht vorhanden.

```
create or replace trigger customers_audit_trigger
  after delete
  on customers
  for each row
declare
  transaction_type varchar2(10);
begin
  transaction_type := case
    when updating then 'update'
    when deleting then 'delete'
  end;

  insert into audits(
    table_name,
```

## Instead-Of-Trigger

```
create or replace trigger create_customer_trigger
  instead of insert on customers_and_contacts
  for each row
declare
  current_customer_id number;
begin
  insert into customers(
    name,
    address,
    website,
    credit_limit
  ) values (
    :new.name,
    :new.address,
    :new.website,
    :new.credit_limit
```

*menhir*

Wenn einem der Syntax schon nicht kompliziert genug ist, dann darf man vor das declare-Statement eines Triggers auch noch folgendes sinnloses Konstrukt packen und statt `:new :neu` schreiben:

```
referencing new as neu old as alt
```

Danach hat man auch fünf Zeilen. Und fünf Hirnzellen weniger.

Wo wir schon dabei sind: Ist der sonst universelle Negations-Operator `!=` zu einfach? Zu simpel und zu verständlich? Wie wäre es mit `<>`; macht das genau selbe, ist aber komplizierter™!